


耐塵試驗機

Dust test chamber

- 符合自動車部品、電氣部品對於塵埃的耐久性。
- 浮游式的防塵及耐塵試驗。
- 採用大型透明壓克力視窗(尺寸W60cm×H70cm)，方便直接觀測內部試品狀況。
- 粉塵數據符合JIS-D-0207-F2規範。
- 濕度採用直讀及免加水SENSOR。
- 數位設定、操作簡便、保養容易。
- Provides a ready-made solution to common dust tests for automotive and electronic industry requirements.
- Suspension dust-proof test.
- Adopt large viewing glass(Size: W60cm×H70cm) can let operator see the specimen clearly.
- Use electronic sensor and humidity displayed in the control panel directly.
- Digital setting, operating easy, maintenance quickly.



MODEL NO. MEANING:
GSDT-1000-F



SPECIFICATION

Model	GSDT-1000-F			GSDT-1000-C		
Internal Dimension (W×H×D)cm	100×100×100			100×100×100		
External Dimension (W×H×D)cm	135×196×135			135×196×135		
Testing Type	(JIS D0207/CNS7139)之F類			(JIS D0207/CNS7139)之C類		IEC529 第二類碼IP5X
	F1	F2	F3	C1	C2	
灰塵之濃度mg/m3 Concentration of dust	60,000 以上	3,000 以上	100 以上	5,000 以上	100 以上	2kg Talcum Powder (75µm以下)
試驗溫度 Testing Temp.	20°C±15°C					
濕度範圍 Humidity Range	45%RH~85%RH					
灰塵流速m/s Flow rate of dust	不予規定(No limited)			5m/s	10m/s	不予規定 (No limited)
試驗時間 Testing Time	攪拌時間Swirl time	5 S或其它			NO	
	休息時間Rest time	15 Mins或其它				
	總計時間Total time	5H	8H	8H	2H	6H
材質 Material	內箱Internal	SUS#304				
	外箱External	SUS#430+Powder coated				
試驗用灰塵 Test Dust	Portland Cement / Talcum Powder					Talcum Powder (75µm以下)
其它附件 Accessories	Chamber lamp, Wiper, Casters with adjusters.					
電源 Power source	1Phase AC220V 50/60HZ, 4K.W.					

*Comply with JIS D0207 CNS D7139, IEC529第二類碼IP5X..